



Standards and **Approvals**

C Cat. III

EN 420:2003 + A1:2009





EN 374-1:2016/ Type A



FN 374-5:2016





CUT





High visibility

Waterproof







Chemical Protective Gloves with Cut Resistance

114.9015

Bonded with 360° Anti-Cut Typhoon® Liner

- Nitrile offering liquid-proof barrier and protection against a wide range of chemicals and high abrasion-resistant durability.
- EN 374:2016/Type A high chemical resistance. The Nitrile coating offers ≥ 480 minutes of permeation time for n-Heptane found in oil-based muds.
- · High visibility green for maximum safety.
- Tested according to EN 388:2016 (mechanical and impact protection) and EN 374:2016 (chemical protection).
- Heat resistant up to 100°C for 15 seconds.

Suitable for:

Oil & Gas: Upstream, Transportation, Downstream and Clean Up | Sewage/Draining Facilities | Water Treatment Facilities.















INDUSTRY:

Agriculture

Building and Construction

Chemical

Maintenance

Oil, Gas and Mining

Waste/recycling

STANDARDS AND APPROVALS:

EN 420:2003 + A1:2009

EN 374:2016

EN 407:2004

ANSI/ISEA 105-2016

EN 388:2016+A1:2018

CE Cat.III

PROTECTION AND **RESISTANCE:**

Abrasion Resistant

Chemical Protection

Cut Resistant

Waterproof

Oil Repellent

Tear Resistant

Puncture Resistant

FEATURES AND PROPERTIES:

Extra long

High visibility

Precision

PRODUCT DETAILS

PACKING / TRANSPORT

Sales Units Per Bundle: 6

Sales Units Per Outer Case: 36

| Material: | Nitrile |
|------------------|----------------|
| Liner material : | Typhoon® |
| Lining type : | Fully lined |
| Grip design : | Raised diamond |
| Grip: | Dry, Wet, Oil |

| Glove fit : | Loose fit |
|-------------|---|
| Size : | 8/M 9/L 10/XL 11/XXL 12/XXXL |
| Length: | 38 cm |
| Thickness : | 1.55 mm |
| Color: | Green |
| | |