



116.599

Cut Resistant Gloves Protector

Typhoon® fibre with a double dipped sandy nitrile coating



• Provides extreme blade cut resistance, EN 388:2016, level F (highest level).

Handling parts with sharp, rough edges | Handling sharp metal sheets | Cutting glass |

- Excellent abrasion and tear resistance.
- Double dipped sandy nitrile coating for superior abrasion resistance.
- Thumb crotch reinforcement.
- Very flexible, dexterous and comfortable fit.
- Typhoon[®] is one of the strongest fibres in the world.
- Ideal for precision handling in oily conditions.

Metal working and assembly operations etc.

OEKO-TEX[®] 100 Approved.

Standards and **Approvals**





















Suitable for:

Thumb base reinforcemen



INDUSTRY:

Automotive

Building and Construction

Glass

Oil, Gas and Mining

Pulp and Paper

Steel and Metal

STANDARDS AND APPROVALS:

EN 420:2003 + A1:2009

EN 388:2016+A1:2018

ANSI/ISEA 105-2016

OEKO-TEX® Standard 100

Color:

CE Cat.II

PROTECTION AND RESISTANCE:

Abrasion Resistant

Cut Resistant

Puncture Resistant

Tear Resistant

Black, Grey

FEATURES AND PROPERTIES:

Breathable

Precision

Thumb base reinforcement

PRODUCT DETAILS

Coating material: Nitrile Coating type : Palm coated Grip: Dry, Wet, Oil Glove fit: Tight fit Size : 7 | 8 | 9 | 10 | 11 | 12 PACKING / TRANSPORT

Sales Units Per Bundle: 12

Sales Units Per Outer Case: 144