



**EN ISO 20344:2011**

ATLANTIDA  
**ELDORADO**  
80117-08L

**S3 HRO HI WR SRC**

**Size:** 38-48  
**Weight:** 765 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Engineering, Farming and  
Gardening



**FEATURES**

- UPPER**  
Full Grain-Anilina Leather-Hydro  
1,8-2,0 mm  
Reflex insert
- LINING**  
3D Air circulation 320 gr.
- ANTISLIP LINING**  
DUALMICRO
- INSOLE**  
Climaction-Fit 337
- TOE CAP**  
Fiber cap SXT
- RESISTANCE TO PERFORATION**  
Textile resistant to 3.0 mm nail
- SOLE**  
**PU-RUBBER VIBRAM-HRO**  
Sole with anti-wear scaff cap.  
Outsole in VIBRAM rubber,  
resistant to 300° C by contact  
(HRO), to acids and oils. Design  
with self-cleaning outsole, with  
Antislip standard.
- TYPE**  
Ankle boot

**TECHNOLOGIES**


- Removable Insole**  
**climaction fit**  
337  
Removable anatomic and ergonomic  
insole. Absorbent and transpiring  
open-cell foam support. Keeps feet  
fresh. Specifically-designed  
thermoforming for exceptional  
comfort.
- Protection elements**  
**RESISTANT TO 3.0 mm. NAILS**  
**fibercap sxt**  
Composite toe cap with fiberglass.  
Resistant to over 200J. Non metal  
perforation resistant insert to over  
1100 N with a 3.0 mm truncated cone  
nail. Protection over the entire sole of  
the foot. Flexible and comfortable



- Lateral stability**  
**dynamic HC control technology**  
Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.
- Torsional stability**  
**STABIL•ACTIVE**  
Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



- Electrical features**  
**WED**  
Wire Electricity Discharge  
Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.
- Other**  
**DUALMICRO**  
Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



**SRC (SRA+SRB)**

SOLE 80  
**PU - RUBBER**

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.43</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.19</b>
		<b>0.13</b>

EN ISO 20344:2011