



EN ISO 20345:2011



POLAR

ELDORADO ARCTIC GRIP®

89117-15L

S3 HRO HI WR CI SRC

Size: 38-48 Weight: 810 gr.

Fit: 11

Working Environment:

Cold places, Wood-metal carpentry, Mountains, Building



Composite toecap with fiberglass.

Resistant to over 200J. Non metal

perforation resistant insert to over

the foot. Flexible and comfortable

. 1100 N with a 3.0 mm truncated cone

nail. Protection over the entire sole of

fibercap **SX**t

Protection elements

FEATURES

UPPER

Pu Hydro Coated Leather 1,8-2,0 Full Grain-Anilina Leather-Hydro 1,8-2,0 mm Reflex insert

LINING

3D Air circulation 320 gr. GenuineWool Polar

ANTISLIP LINING

DUALMICRO

INSOLE

Dual insulation

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Ankle boot

SOLE PU-RUBBER VIBRAM- ARCTIC

New polymer blend with an advanced filler system. Engineered for low temperature use. Improved grip on ice or snow.VIBRAM performance, quality and durability. Self-cleaning outsole, designed to all types of ground better.With scaff cap.

TECHNOLOGIES

Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.





houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability (S) STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater



Auesto documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale

Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.





The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user





Lateral stability

Ergonomic rigid internal structure. It





SRC (SRA+SRB)

~~~~	Common of the second	SOLE 89 PU - RUBBER ARCTIC GRIP	
SRA CERAMIC	FLAT ≥ <b>0.32</b>	0.62	
DETERGENT SOLUTION	HEEL (CONTACT ANGLE 7°) ≥0.28	0.59	
SRB	FLAT ≥0.18	0.22	EN ION 2037.4-2011
GLYCEROL	HEEL (CONTACT ANGLE 7°) ≥0.13	0.20	EN ION 2