



EN ISO 20345:2011



RITMO  
**CUBAN BOA®**  
91373-00L

**S3 SRC**

**Size:** 35-48  
**Weight:** 520 gr.

**Fit:** 11

**Working Environment:**  
Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas



## FEATURES

### UPPER

MicroFiber Suede with Pro-tech SXT light

### LINING

3D Air circulation 320 gr.

**ANTISLIP LINING**  
DUALMICRO

### INSOLE

Five 4 Fit

### TOE CAP

Alu SXT 2.0 Toe cap

### RESISTANCE TO PERFORATION

Zero(K) Perforation resistant

### TYPE

Low Shoe

### SOLE

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole

**FIVE 4 FIT**

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements

**ZERO(k)**  
ANTIPERFORATION

**alu-sxt2.0**  
aluminium

A new aluminium multi-thicknesses toecap, which delivers a highly performing protection where needed. Resistant to impact of over 200J. Non Metallic anti-perforation insert. Resistant to over 1100 N with zero perforation.



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other



**FIT TO GO FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



## SRC (SRA+SRB)



SOLE 91  
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.54 0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.29 0.23

EN ISO 20344:2011